

FLINTLASTIC® SA

CertainTeed **Flintlastic® SA** is a premium quality self-adhering SBS modified bitumen roofing system that consists of a nailable base with a top surface designed to accept self-adhering membrane, a self-adhering mid-ply, and a self-adhering cap. For small projects such as decks, additions and porches, two-ply systems comprising **Flintlastic SA NailBase** and **Flintlastic SA Cap Sheet** may be appropriate. For larger roofs and commercial applications, three-ply



systems comprising all three **Flintlastic SA** layers are recommended. CertainTeed also offers **FlintFlash™ SA** pre-cut flashing rolls for an integrated approach to flashing details. Roofs built to CertainTeed roof system specifications provide the best in longevity and performance.

Color Companion System

Flintlastic SA is available in a variety of colors that complement eight of the most popular CertainTeed shingle colors. Now it's easy to coordinate roofs on carports, porches and other low slope areas with the shingles on the home's primary roof.



Product Features

- Ease of application
- No special installation tools or equipment needed
- No hot asphalt or torches required
- Cleaner, neater work environment
- Available in:
 - 12 year warranty:
 - Flintlastic SA NailBase and Flintlastic SA Cap
 - Flintlastic SA Mid Ply or SA PlyBase and Flintlastic SA Cap (for non-nailable substrates)
 - 15 year warranty:
 - Flintlastic SA NailBase or SA PlyBase
 - Flintlastic SA Mid Ply and Flintlastic SA Cap

Specifications

Roll dimensions — 66'6" x 39'-3/8" (base); 33'11" x 39'-3/8" (mid ply and cap); 33'11" x 13-1/8" or 9-3/4" (FlintFlash)

Thickness — 1.5 mm (base); 3.0 mm (mid ply and FlintFlash); 4.0 mm (cap)

Weight — 84 lbs. (base); 68 lbs. (mid ply); 97 lbs. (cap); 22.5 lbs. or 17 lbs. (FlintFlash)

Coverage — 2 squares (base); 1 square (mid ply and cap); 1/3 or 1/4 square (FlintFlash)